

LS stone former survey 19C 87 $\frac{2}{3}$ L
Stake 100 Count Point Total Dis 59C 60 L
19C 87 $\frac{2}{3}$ L
19C 87 $\frac{2}{3}$ L
LS stone former survey 2

FIELD NOTES.

Corners	Bearing Trees	Inches in Diameter	Courses They Bear	Links Distant	Character of Lands	REMARKS	Corners	Bearing Trees	Inches in Diameter	Courses They Bear	Links Distant	Character of Lands	REMARKS	
						Record of Survey of line as shown above surveyed for L. H. Blockman & H. Schmidt. Agreement below the above parties this line was to be a straight line between the two points marked 1 & 2 (NW cor SW $\frac{1}{4}$, SE $\frac{1}{4}$, Sec 12-88-11.) I found both corners marked by L. Stone. I then run line between the two points being able to see the whole distance, and set dunnies as shown by above Plat. I also found L. Stone at NW cor SW $\frac{1}{4}$, SE $\frac{1}{4}$, Sec 12-88-11 it being 14 Lks West and 4 $\frac{1}{2}$ Lks South from the dunnies of line run by me. But as this line was by agreement I did not use this mark								

The $S \frac{1}{2}$ of Section 12, Township 88, Range 11, West 5th P. M., Iowa, was surveyed by me on the 2 day of May 1913, at request of Fred Cornforth & Self, were chainmen duly approved and sworn by me on the 12 day of May 1913, and the above is a true and correct plat and field notes of the said survey.
D. E. Boyack Co. Engineer & County Surveyor.
Blockman Co