

53+149 = N.E. cor. sec. 26-87-11 - CM 31.2

53+141 = P. & S. E. l. pt. P.L.

53+141  
5314.9  
2656.9  
2658.2

1328.9  
Projected pt.  
53+141  
5314.9  
2656.9  
2658.2

39+90.4 = Prorated Point  
39+80.7 = F. R. F.

1325.9  
2651.8  
2654.8  
5306.6  
5285.6  
27.6  
1333.7 = Prorated Corner

26+75.5 = N. R.O.W. for R.W.  
26+56.7 = E. 1/4 26-87-11; Found Nigger head 1/4 x 1/4 x 0.5, 7.4 W.R.L.  
26+54.8 = I.B. setting Co. Engrs. (D.P.) 2.6' E. of R.L.

26+32.7 = S. R.O.W. for R.W.  
26+51.8 = Prorated point

19+86.3 =  
1329.5  
1324.6 = Prorated Point

13+27.2 = 1/4 1/4 for R.W. Found Nigger head 0.7 W.R.L.  
2659.0  
56.7  
2.3

4+32.2 = Fc. R.W.  
4+30.9 = Prorated Dist. backwards  
10.7 = N. R.O.W. for R.W.

1700 = N.E. cor. sec. 26-87-11 - CM 0.27 R.L.  
0-2.3 = NE 35-87-11, 8.8' W.R.L.

