

5355
5342.5

2521.6

5296.2
46.3

5342.5 = fr. South to Co. Pol. 3' N.R.L.
5342.5 = Asst. Sec. 30. of fence 9.3' under
5296.2 = double Dist. to true corner water 4.0 deep.

51439.25 = R.L. from South

48474.57 = E Bank of River 0.65 N to RR

46476.3 = W. Bank of River 1.55 N to RR

39483.79 = Nail 6.95' S. of to

37421.5 = E.R.O.W. to R.I. R.R. 7.75 N to corp.

37402.25 = Q. of R.I. R.R. Track

36477.65 = W.R.O.W. to R.I. R.R.

31400 = fr. 6.25' N. of R.L.

29451.4 = E Bank of River corp. 12.4 N. R.L.

28400.0 = W Bank of River

26448.1 = set stake 28.3' N. of R.L.

24441.7 = Red Head on R.L. Set with Cor. 5.9 N.R.L.

20400.0 = Pipe to fr. R.L. 8.9' S. of to

17491.98 = E. R.O.W. to R. N. 46. R.L. 6.3' S. of to corp.

13426.9 = Iron pipe 6.95' N. of R.L.

don't believe this is any good

12496.2 = W. R.O.W. to R. N. 46

0410 = N.E. cor. sec. 32-90-14 S.C.M. set

April 26, 1941
T. Bowser, Notes 95.

